

Flowmeters

Precision Medical offers a full line of medical flowmeters from neonatal to adult clinical uses. Flowmeters are available in Oxygen and Medical Air and come standard with 1/8" Female NPT connection. All flowmeters can be fitted with different quick connects and configurations including dual Y Blocks and T Branches, Power Take Offs, Eliminators and Neb Blocks.



Chrome Flowmeter Model Series (1MFA, 4MFA, 6MFA)

The Chrome Series Flowmeter is a pressure compensation flowmeter designed to meet strict global standards of durability and accuracy. The polycarbonate flow tube assures consistent readings and allows superb accuracy for precise low and high flow requirements. The low flow model is labeled with a stork that clearly identifies its application in neonatal environments. The large knurled knobs come in green for oxygen and yellow for air and are marked with O₂ and Air for easy identification.

Compact Flowmeter Model Series (8MFA)

The Compact Series Flowmeter has a polycarbonate housing that extends over the lightweight aluminum body providing superior durability. Its state-of-the-art housing incorporates a white backdrop that allows accurate adjustments and reading of the flow setting. The contemporary design results in a smaller flowmeter that fits more easily into space-cramped wall rails. The flow control knobs are on the front of the flowmeter in clear sight of the clinician and marked by gas type for added safety. Available in both air and oxygen models.



Select Flowmeter Model Series (3MFA)

The Select Flowmeter combines the durability of a metal flowmeter with its male connection along with a durable nylon body and allows you to direct the output of the flowmeter to any one of the three outlet connections. With multiple ports, the Select Flowmeter allows you to leave the cannula, humidifier, and nebulizer hooked up to the outlet for easy treatment whenever needed. Nebulizer treatments can be delivered without disconnecting the humidifier. Available in oxygen only.



Dial Flowmeter Model Series (7MFA)

The Dial Flowmeter is compact and allows the tubeless flowmeter to fit into tight headwalls and makes it virtually damage proof when other equipment is installed. The knurled flow adjustment knob and the large easy-to-read numbers make flow adjustments simple. The dial flowmeter can be mounted on headwall outlets and ceiling mount drops. Available in both air and oxygen models.

Available Fittings

Precision Medical offers a full line of medical fittings, quick connects and DISS fittings for all medical gases including Oxygen, Air, Vacuum, Nitrous Oxide, Nitrogen, Carbon Dioxide, and WAGD.

	DISS Female Hex Nut	DISS Female Hand Tight	DISS Male	Ohmeda	Chemtron	Oxequip	Schrader	Puritan Bennett	Medstar
O ₂									
	0106	0110	0701	2101	3101	5101	6101	4101	8101
Air									
	0207	0209	0731	2201	3201	5201	6201	4201	8201

Chrome Flowmeters



1MFA1102-L



1MFA1001



1MFA8002-R



1MFA2001PTO



1MFA2001



1MFA8001PTO

Ordering Information

	O ₂ 0-200 cc	O ₂ 0-1 l/min	O ₂ 0-3.5 l/min	O ₂ 0-5 l/min	O ₂ 0-15 l/min	O ₂ 2-26 l/min	O ₂ 0-70 l/min	Air 0-15 l/min	Air 0-70 l/min
No Adaptor (1/8" NPT Female) with PTO	6MFA1001	4MFA1001	1MFA3001	1MFA3501	1MFA1001	1MFA1101	1MFA8001	1MFA2001	1MFA9001
	6MFA1001PTO	4MFA1001PTO	1MFA3001PTO	1MFA3501PTO	1MFA1001PTO	1MFA1101PTO	1MFA8001PTO	1MFA2001PTO	1MFA9001PTO
DISS Female Hex Nut with PTO	6MFA1002	4MFA1002	1MFA3002	1MFA3502	1MFA1002	1MFA1102	1MFA8002	1MFA2002	1MFA9002
	6MFA1002PTO	4MFA1002PTO	1MFA3002PTO	1MFA3502PTO	1MFA1002PTO	1MFA1102PTO	1MFA8002PTO	1MFA2002PTO	1MFA9002PTO
with right inlet	6MFA1002-R	4MFA1002-R	1MFA3002-R	1MFA3502-R	1MFA1002-R	1MFA1102-R	1MFA8002-R	1MFA2002-R	1MFA9002-R
with left inlet	6MFA1002-L	4MFA1002-L	1MFA3002-L	1MFA3502-L	1MFA1002-L	1MFA1102-L	1MFA8002-L	1MFA2002-L	1MFA9002-L
DISS Female Hand Tight with PTO	6MFA1003	4MFA1003	1MFA3003	1MFA3503	1MFA1003	1MFA1103	1MFA8003	1MFA2003	1MFA9003
	6MFA1003PTO	4MFA1003PTO	1MFA3003PTO	1MFA3503PTO	1MFA1003PTO	1MFA1103PTO	1MFA8003PTO	1MFA2003PTO	1MFA9003PTO
with right inlet	6MFA1003-R	4MFA1003-R	1MFA3003-R	1MFA3503-R	1MFA1003-R	1MFA1103-R	1MFA8003-R	1MFA2003-R	1MFA9003-R
with left inlet	6MFA1003-L	4MFA1003-L	1MFA3003-L	1MFA3503-L	1MFA1003-L	1MFA1103-L	1MFA8003-L	1MFA2003-L	1MFA9003-L
DISS Male with PTO	6MFA1004	4MFA1004	1MFA3004	1MFA3504	1MFA1004	1MFA1104	1MFA8004	1MFA2004	1MFA9004
	6MFA1004PTO	4MFA1004PTO	1MFA3004PTO	1MFA3504PTO	1MFA1004PTO	1MFA1104PTO	1MFA8004PTO	1MFA2004PTO	1MFA9004PTO
Ohmeda with PTO	6MFA1005	4MFA1005	1MFA3005	1MFA3505	1MFA1005	1MFA1105	1MFA8005	1MFA2005	1MFA9005
	6MFA1005PTO	4MFA1005PTO	1MFA3005PTO	1MFA3505PTO	1MFA1005PTO	1MFA1105PTO	1MFA8005PTO	1MFA2005PTO	1MFA9005PTO
Chemtron with PTO	6MFA1006	4MFA1006	1MFA3006	1MFA3506	1MFA1006	1MFA1106	1MFA8006	1MFA2006	1MFA9006
	6MFA1006PTO	4MFA1006PTO	1MFA3006PTO	1MFA3506PTO	1MFA1006PTO	1MFA1106PTO	1MFA8006PTO	1MFA2006PTO	1MFA9006PTO
Oxequip with PTO	6MFA1007	4MFA1007	1MFA3007	1MFA3507	1MFA1007	1MFA1107	1MFA8007	1MFA2007	1MFA9007
	6MFA1007PTO	4MFA1007PTO	1MFA3007PTO	1MFA3507PTO	1MFA1007PTO	1MFA1107PTO	1MFA8007PTO	1MFA2007PTO	1MFA9007PTO
Puritan-Bennett with PTO	6MFA1008	4MFA1008	1MFA3008	1MFA3508	1MFA1008	1MFA1108	1MFA8008	1MFA2008	1MFA9008
	6MFA1008PTO	4MFA1008PTO	1MFA3008PTO	1MFA3508PTO	1MFA1008PTO	1MFA1108PTO	1MFA8008PTO	1MFA2008PTO	1MFA9008PTO
Schrader with PTO	6MFA1009	4MFA1009	1MFA3009	1MFA3509	1MFA1009	1MFA1109	1MFA8009	1MFA2009	1MFA9009
	6MFA1009PTO	4MFA1009PTO	1MFA3009PTO	1MFA3509PTO	1MFA1009PTO	1MFA1109PTO	1MFA8009PTO	1MFA2009PTO	1MFA9009PTO
Medstar with PTO	6MFA100M	4MFA100M	1MFA300M	1MFA350M	1MFA100M	1MFA110M	1MFA800M	1MFA200M	1MFA900M
	6MFA100MPTO	4MFA100MPTO	1MFA300MPTO	1MFA350MPTO	1MFA100MPTO	1MFA110MPTO	1MFA800MPTO	1MFA200MPTO	1MFA900MPTO

Features

Highly accurate needle valves ensure precise flow-settings

Green knob with O₂ marking and Yellow knob with AIR marking for easy identification

Durable polycarbonate housing

Supply pressure of 50 psi

Air and oxygen models available

Warranty

Lifetime warranty on flow tube and housing

5-years on needle valve

1-year on all other parts

Product Specifications

Flowmeters calibrated at 50 PSI, 70°F, standard atmospheric pressure. Specifications are subject to change without prior notice.

Flow Range	Gas	Increments	Accuracy	Flush Flow
0-200 cc	Oxygen	20 cc	0-100 cc ±10 cc 101-200 cc ±14 cc	500 cc
0-1 l/min	Oxygen	0.1 l/min	0-1 ±0.05 l/min	5 l/min
0-3.5 l/min	Oxygen	0.125 (0-1) l/min 0.25 (1-3.5) l/min	0-3.5 ±0.15 l/min	20-40 l/min
0-5 l/min	Oxygen	0.25 l/min	0-5 ±0.20 l/min	60-80 l/min
0-15 l/min	Oxygen	0.5 (0-5) l/min 1 (5-15) l/min	0-5 ±0.25 l/min 6-15 ±0.50 l/min	60-80 l/min
2-26 l/min	Oxygen	1 l/min	2-4 ±0.50 l/min 5-26 ±10% of reading	60-80 l/min
3-35 l/min	Oxygen	1 (3-15) l/min 5 (15-35) l/min	3-4 ±0.50 l/min 5-35 ±10% of reading	—
0-70 l/min	Oxygen	5 l/min	0-70 ±10% of reading	70-90 l/min
0-15 l/min	Air	0.5 (0-5) l/min 1 (5-15) l/min	0-5 ±0.25 l/min 6-15 ±0.50 l/min	60-80 l/min
0-70 l/min	Air	5 l/min	0-70 ±10% of reading	70-90 l/min

Need something else?

Custom configurations, international specifications, and color options are available.
Contact Customer Service at 1-800-272-7285 for custom requests and more information.

Compact Flowmeters



8MFA4001



8MFA1001



8MFA1001PTO



8MFA2001PTO



8MFA2001

Ordering Information

	O ₂ 0-8 l/min	O ₂ 0-15 l/min	Air 0-15 l/min
No Adaptor (1/8" NPT Female)	8MFA4001	8MFA1001	8MFA2001
DISS Female Hex Nut	8MFA4002	8MFA1002	8MFA2002
DISS Female Hand Tight	8MFA4003	8MFA1003	8MFA2003
DISS Male	8MFA4004	8MFA1004	8MFA2004
Ohmeda	8MFA4005	8MFA1005	8MFA2005
Chemetron	8MFA4006	8MFA1006	8MFA2006
Oxequip	8MFA4007	8MFA1007	8MFA2007
Puritan-Bennett	8MFA4008	8MFA1008	8MFA2008
Schrader	8MFA4009	8MFA1009	8MFA2009
Medstar	8MFA400M	8MFA100M	8MFA200M

For MRI Conditional Compact Series Flowmeters, please contact customer service at 1-800-272-7285

Features

Highly accurate needle valves ensure precise flow settings

Lightweight aluminum body

Green knob with O₂ marking and Yellow knob with AIR marking for easy identification

Stamped AIR and O₂ on side of flowmeter body

Smaller profile and design fits more easily into space-cramped wall rails

Durable polycarbonate housing

Supply pressure of 50 psi

Air and oxygen models available

Warranty

Lifetime warranty on flow tube and housing

5-years on needle valve

1-year on all other parts

Product Specifications

Flowmeters calibrated at 50 PSI, 70°F, standard atmospheric pressure. Specifications are subject to change without prior notice.

Flow Range	Gas	Increments	Accuracy	Flush Flow
0-8 l/min	Oxygen	0.5 l/min (starts at 0.5 l/min)	± 0.25 l/min	40-60 l/min
0-15 l/min	Oxygen	0.5 l/min from 0.5 to 5 l/min	± 0.25 l/min from 0.5 to 5 l/min	40-60 l/min
		1 l/min from 5 to 15 l/min	± 0.5 l/min from 6 to 15 l/min	
0-15 l/min	Air	0.5 l/min from 0.5 to 5 l/min	± 0.25 l/min from 0.5 to 5 l/min	40-60 l/min
		1 l/min from 5 to 15 l/min	± 0.5 l/min from 6 to 15 l/min	

Need something else?

Custom configurations (including power take offs and right/left elbows), international specifications, and color options are available.

Contact Customer Service at 1-800-272-7285 for custom requests and more information.

Dial Flowmeters



7MFA2001



7MFA1001TC



7MFA1001

Product Specifications

NOTE: There is no flow between settings

Flow Range	Position Increments (l/min)
0-15 l/min	Off, 0.5, 1, 2, 3, 4, 5, 6, 8, 10, 15, and Flush
0-25 l/min	Off, 1, 2, 3, 4, 6, 8, 10, 12, 15, 20 and 25

Ordering Information

	O ₂ 0-15 l/min	O ₂ 0-25 l/min	Air 0-15 l/min	Air 0-25 l/min
No Adaptor (1/8" NPT Female)	7MFA1001	7MFA1101	7MFA2001	7MFA2101
DISS Female Hex Nut	7MFA1002	7MFA1102	7MFA2002	7MFA2102
DISS Female Hand Tight	7MFA1003	7MFA1103	7MFA2003	7MFA2103
DISS Male	7MFA1004	7MFA1104	7MFA2004	7MFA2104
Ohmeda	7MFA1005	7MFA1105	7MFA2005	7MFA2105
Chemetron	7MFA1006	7MFA1106	7MFA2006	7MFA2106
Oxequip	7MFA1007	7MFA1107	7MFA2007	7MFA2107
Puritan-Bennett	7MFA1008	7MFA1108	7MFA2008	7MFA2108
Schrader	7MFA1009	7MFA1109	7MFA2009	7MFA2109
Medstar	7MFA100M	7MFA110M	7MFA200M	7MFA210M

* Add TC after part number for Top Connection

Select Flowmeters



3MFA1001



Features

Available in flow ranges
0.5-15 l/min and 1-25 l/min

Available in oxygen and air

Warranty

Lifetime warranty on flow tube
and housing

5-years on needle valve

1-year on all other parts

Need something else?

Custom configurations (including
top connections, power take offs,
and right/left elbows), international
specifications, and color options
are available.

Contact Customer Service at
1-800-272-7285 for custom requests
and more information.

Features

Available in flow ranges
0.5-5 l/min and 1-25 l/min

Available in oxygen

Warranty

Lifetime warranty on flow tube
and housing

5-years on needle valve

1-year on all other parts

Need something else?

Custom configurations
(including power take offs),
international specifications, and
color options are available.

Contact Customer Service at
1-800-272-7285 for custom requests
and more information.

Product Specifications

Flowmeters calibrated at 50 PSI, 70°F, standard
atmospheric pressure. Specifications are subject to
change without prior notice.

Flow Range	0-15 l/min
Gas	Oxygen
Increments	0.5 l/min from 0.5 to 5 l/min
	1 l/min from 5 to 15 l/min
Accuracy	± 0.25 l/min from 0.5 to 5 l/min
	± 0.5 l/min above 6 to 15 l/min
Flush Flow	60-80 l/min

Ordering Information

	Select Flowmeter
No Adaptor (1/8" NPT Female)	3MFA1001
DISS Female Hex Nut	3MFA1002
DISS Female Hand Tight	3MFA1003
DISS Male	3MFA1004
Ohmeda	3MFA1005
Chemetron	3MFA1006
Oxequip	3MFA1007
Puritan-Bennett	3MFA1008
Schrader	3MFA1009
Medstar	3MFA100M

Flowmeter Y Block



Y1MFA2001PT2



Y8MFA1001

Ordering Information

	Compact O ₂ 0-15 l/min	Chrome O ₂ 0-15 l/min	Compact Air 0-15 l/min	Chrome Air 0-15 l/min
No Adaptor (1/8" NPT Female)	Y8MFA1001	Y1MFA1001	Y8MFA2001	Y1MFA2001
DISS Female Hex Nut	Y8MFA1002	Y1MFA1002	Y8MFA2002	Y1MFA2002
DISS Female Hand Tight	Y8MFA1003	Y1MFA1003	Y8MFA2003	Y1MFA2003
DISS Male	Y8MFA1004	Y1MFA1004	Y8MFA2004	Y1MFA2004
Ohmeda	Y8MFA1005	Y1MFA1005	Y8MFA2005	Y1MFA2005
Chemetron	Y8MFA1006	Y1MFA1006	Y8MFA2006	Y1MFA2006
Oxequip	Y8MFA1007	Y1MFA1007	Y8MFA2007	Y1MFA2007
Puritan-Bennett	Y8MFA1008	Y1MFA1008	Y8MFA2008	Y1MFA2008
Schrader	Y8MFA1009	Y1MFA1009	Y8MFA2009	Y1MFA2009
Medstar	Y8MFA100M	Y1MFA100M	Y8MFA200M	Y1MFA200M

Need something else?

Custom configurations (including power take offs and other flowmeter configurations), international specifications, and color options are available.

See Compact or Chrome Flowmeters for specifications

Contact Customer Service at 1-800-272-7285 for custom requests and more information.

The DISS “Y” block assembly allows two chrome or two compact flowmeters to be installed using one wall outlet. Constructed of lightweight aluminum, the Y Block is used to deliver oxygen or medical air to two separate clinical areas. The optional power take off (demand valves) allows the attachment of a ventilator, flowmeter, resuscitation bag or suction regulator.

Y-Blocks are available in and chrome and compact flowmeter and can be ordered as 1/8" NPT Female and 1/4" NPT Female.

Warranty

1-year on Y Block

Chrome Flowmeter T Branch

The DISS “T” branch assembly allows two chrome flowmeters to be installed using one wall outlet. Constructed of lightweight aluminum, the T Branch is used to deliver oxygen or medical air to two separate clinical areas.

The optional power take off (demand valves) allows the attachment of a ventilator, flowmeter, resuscitation bag or suction regulator. The T Branch comes centered to the wall outlet or can be ordered offset to the right or left.

T-Branches are available in chrome flowmeter with 1/8" NPT Standard and 1/8" NPT Offset

Warranty

1-year on T Branch



D1MFA1001PT2

Ordering Information

	Chrome O ₂ 0-15 l/min	Chrome Air 0-15 l/min
No Adaptor (1/8" NPT Female)	D1MFA1001	D1MFA2001
DISS Female Hex Nut	D1MFA1002	D1MFA2002
DISS Female Hand Tight	D1MFA1003	D1MFA2003
DISS Male	D1MFA1004	D1MFA2004
Ohmeda	D1MFA1005	D1MFA2005
Chemetron	D1MFA1006	D1MFA2006
Oxequip	D1MFA1007	D1MFA2007
Puritan-Bennett	D1MFA1008	D1MFA2008
Schrader	D1MFA1009	D1MFA2009
Medstar	D1MFA100M	D1MFA200M

Need something else?

Custom configurations (including power take offs and other flowmeter configurations), international specifications, and color options are available.

See Compact or Chrome Flowmeters for specifications

Contact Customer Service at 1-800-272-7285 for custom requests and more information.

Eliminator with Flowmeter



1MFA7150



E7150

Features

- Eliminates continuous oxygen flow waste
- Lifting the resuscitation bag instantly starts oxygen flow
- Available in 3 preset, adjustable flow rates
- Can be mounted on left or right hanger location

Warranty

1-year on Eliminator

The Eliminator with Flowmeter works by turning on oxygen flow when the resuscitation bag is lifted from its hanger. Available with either chrome or compact flowmeters, the Eliminator is installed off-set left to the flowmeter and can be ordered with all standard outlet styles. For offset right of the flowmeter, add (-R) to the part number.

The standard Eliminator configuration is available in three preset flows. A fixed-flow barb controls flow to the resuscitation bag, the flowmeter operates independent of the Eliminator and can be used for oxygen treatments. Adjustable flow rate is controlled by the 0-15 chrome or 0-15 compact flowmeter.

Ordering Information

	Liter Flow Barb	Eliminator	Eliminator with Chrome Flowmeter	Eliminator with Compact Flowmeter
No Adaptor (1/8" NPT Female)	15 l/min	E7150	1MFA7150	8MFA7150
	24 l/min	E7240	1MFA7240	8MFA7240
	FLUSH	E7000	1MFA7000	8MFA7000
	Adjustable	E7990	1MFA7990	8MFA7990
DISS Female Hex Nut	15 l/min	E7152	1MFA7152	8MFA7152
	24 l/min	E7242	1MFA7242	8MFA7242
	FLUSH	E7002	1MFA7002	8MFA7002
	Adjustable	E7992	1MFA7992	8MFA7992
DISS Female Hand Tight	15 l/min	E7153	1MFA7153	8MFA7153
	24 l/min	E7243	1MFA7243	8MFA7243
	FLUSH	E7003	1MFA7003	8MFA7003
	Adjustable	E7993	1MFA7993	8MFA7993
DISS Male	15 l/min	E7154	1MFA7154	8MFA7154
	24 l/min	E7244	1MFA7244	8MFA7244
	FLUSH	E7004	1MFA7004	8MFA7004
	Adjustable	E7994	1MFA7994	8MFA7994
Ohmeda	15 l/min	E7155	1MFA7155	8MFA7155
	24 l/min	E7245	1MFA7245	8MFA7245
	FLUSH	E7005	1MFA7005	8MFA7005
	Adjustable	E7995	1MFA7995	8MFA7995
Chemetron	15 l/min	E7156	1MFA7156	8MFA7156
	24 l/min	E7246	1MFA7246	8MFA7246
	FLUSH	E7006	1MFA7006	8MFA7006
	Adjustable	E7996	1MFA7996	8MFA7996
Oxequip	15 l/min	E7157	1MFA7157	8MFA7157
	24 l/min	E7247	1MFA7247	8MFA7247
	FLUSH	E7007	1MFA7007	8MFA7007
	Adjustable	E7997	1MFA7997	8MFA7997
Puritan-Bennett	15 l/min	E7158	1MFA7158	8MFA7158
	24 l/min	E7248	1MFA7248	8MFA7248
	FLUSH	E7008	1MFA7008	8MFA7008
	Adjustable	E7998	1MFA7998	8MFA7998
Schrader	15 l/min	E7159	1MFA7159	8MFA7159
	24 l/min	E7249	1MFA7249	8MFA7249
	FLUSH	E7009	1MFA7009	8MFA7009
	Adjustable	E7999	1MFA7999	8MFA7999
Medstar	15 l/min	E715M	1MFA715M	8MFA715M
	24 l/min	E724M	1MFA724M	8MFA724M
	FLUSH	E700M	1MFA700M	8MFA700M
	Adjustable	E799M	1MFA799M	8MFA799M

Need something else?

Custom configurations, international specifications, and color options are available. Contact Customer Service at 1-800-272-7285 for custom requests and more information.

Neb Block with Flowmeter



1MFA6070



8MFA6100V

The Neb Block with Flowmeter is used for nebulizer

treatments, resuscitation bags, or equipment power. The Neb

Block allows all equipment to be kept connected and ready for

use when needed. Designed for simple operation, the device

begins working by pushing the switch from “OFF” to “ON” to

deliver a nebulizer treatment or to utilize a resuscitation bag.

The outlet barb is available in 6 preset flows for easy delivery

of treatment.

Features

Simple On and Off operation

Available in 6 preset flows

Warranty

1-year on Neb Block

Need something else?

Custom configurations, international specifications, and color options are available. Contact Customer Service at 1-800-272-7285 for custom requests and more information.

Ordering Information

	Liter Flow Barb	Neb Block	Neb Block with Chrome Flowmeter	Neb Block with Compact Flowmeter
No Adaptor (1/8" NPT Female)	6-7 l/min	NB6060	1MFA6060	8MFA6060
	7-8 l/min	NB6070	1MFA6070	8MFA6070
	8-9 l/min	NB6080	1MFA6080	8MFA6080
	10-11 l/min	NB6100	1MFA6100	8MFA6100
	14-16 l/min	NB6150	1MFA6150	8MFA6150
	24-26 l/min	NB6240	1MFA6240	8MFA6240
DISS Female Hex Nut	6-7 l/min	NB6062	1MFA6062	8MFA6062
	7-8 l/min	NB6072	1MFA6072	8MFA6072
	8-9 l/min	NB6082	1MFA6082	8MFA6082
	10-11 l/min	NB6102	1MFA6102	8MFA6102
	14-16 l/min	NB6152	1MFA6152	8MFA6152
	24-26 l/min	NB6242	1MFA6242	8MFA6242
DISS Female Hand Tight	6-7 l/min	NB6063	1MFA6063	8MFA6063
	7-8 l/min	NB6073	1MFA6073	8MFA6073
	8-9 l/min	NB6083	1MFA6083	8MFA6083
	10-11 l/min	NB6103	1MFA6103	8MFA6103
	14-16 l/min	NB6153	1MFA6153	8MFA6153
	24-26 l/min	NB6243	1MFA6243	8MFA6243
DISS Male	6-7 l/min	NB6064	1MFA6064	8MFA6064
	7-8 l/min	NB6074	1MFA6074	8MFA6074
	8-9 l/min	NB6084	1MFA6084	8MFA6084
	10-11 l/min	NB6104	1MFA6104	8MFA6104
	14-16 l/min	NB6154	1MFA6154	8MFA6154
	24-26 l/min	NB6244	1MFA6244	8MFA6244
Ohmeda	6-7 l/min	NB6065	1MFA6065	8MFA6065
	7-8 l/min	NB6075	1MFA6075	8MFA6075
	8-9 l/min	NB6085	1MFA6085	8MFA6085
	10-11 l/min	NB6105	1MFA6105	8MFA6105
	14-16 l/min	NB6155	1MFA6155	8MFA6155
	24-26 l/min	NB6245	1MFA6245	8MFA6245
Chemetron	6-7 l/min	NB6066	1MFA6066	8MFA6066
	7-8 l/min	NB6076	1MFA6076	8MFA6076
	8-9 l/min	NB6086	1MFA6086	8MFA6086
	10-11 l/min	NB6106	1MFA6106	8MFA6106
	14-16 l/min	NB6156	1MFA6156	8MFA6156
	24-26 l/min	NB6246	1MFA6246	8MFA6246
Oxequip	6-7 l/min	NB6067	1MFA6067	8MFA6067
	7-8 l/min	NB6077	1MFA6077	8MFA6077
	8-9 l/min	NB6087	1MFA6087	8MFA6087
	10-11 l/min	NB6107	1MFA6107	8MFA6107
	14-16 l/min	NB6157	1MFA6157	8MFA6157
	24-26 l/min	NB6247	1MFA6247	8MFA6247
Puritan-Bennett	6-7 l/min	NB6068	1MFA6068	8MFA6068
	7-8 l/min	NB6078	1MFA6078	8MFA6078
	8-9 l/min	NB6088	1MFA6088	8MFA6088
	10-11 l/min	NB6108	1MFA6108	8MFA6108
	14-16 l/min	NB6158	1MFA6158	8MFA6158
	24-26 l/min	NB6248	1MFA6248	8MFA6248
Schrader	6-7 l/min	NB6069	1MFA6069	8MFA6069
	7-8 l/min	NB6079	1MFA6079	8MFA6079
	8-9 l/min	NB6089	1MFA6089	8MFA6089
	10-11 l/min	NB6109	1MFA6109	8MFA6109
	14-16 l/min	NB6159	1MFA6159	8MFA6159
	24-26 l/min	NB6249	1MFA6249	8MFA6249
Medstar	6-7 l/min	NB606M	1MFA606M	8MFA606M
	7-8 l/min	NB607M	1MFA607M	8MFA607M
	8-9 l/min	NB608M	1MFA608M	8MFA608M
	10-11 l/min	NB610M	1MFA610M	8MFA610M
	14-16 l/min	NB615M	1MFA615M	8MFA615M
	24-26 l/min	NB624M	1MFA624M	8MFA624M

* Add V after part number for vertical position

* Add R after part number for Neb Drive on the right

Flowmeter Accessories

Night Check

The Night Check is designed to improve patient comfort by allowing clinicians to illuminate a flowmeter without having to turn on additional lighting. The single button illuminates the flowmeter for 10 seconds so clinicians can check the flowmeter flow rates at night or in darker environments. The LED light source uses a replaceable lithium-ion battery and lasts 8-10 years at 4 checks per night.



The Night Check is compatible with Precision Medical 1MFA, 3MFA, 4MFA and 6MFA series flowmeters.

Warranty
1-year

Ordering Information

PM1050: Night Check includes Night Check and one lithium-ion battery
8066: Replacement battery
-NC: Add -NC suffix to flowmeter part number to order flowmeter with Night Check

Flow Selector

The Flow Selector allows clinicians to direct the outlet flow from any standard flowmeter to any one of its three outlets.

The two optional ports allow a cannula, humidifier and nebulizer to remain attached for convenient treatments.



Warranty
1-year

Ordering Information

PM1000: Flow Selector

Oxygen Supply Manifold

Oxygen Supply Manifold provides maximum on-site flexibility for emergency situations requiring multiple oxygen sources and rapid deployment. It can be used in emergency, mass casualty, EMS, and triage situations. The system provides oxygen delivery for 6 patients and allows for easy on-site hook up of any rescue device requiring 50 psi pressure, such as a ventilator, anesthesia machine, or demand resuscitation device.



PM106

Warranty
1-year

Ordering Information

PM106: Includes Oxygen Supply Manifold, one 20 ft. oxygen hose, 6 oxygen therapy masks, 1 hard-shell carrying case
505568: Oxygen Supply Manifold Only

Timox Oxygen Timer

The Timox Oxygen Timer is designed to display and record the amount of time oxygen gas has been flowing to a patient. The digital timer begins when oxygen gas flows at 0.4 l/min or greater. The timer can record up to 1999.9 hours and is easily reset by pressing the "RESET" button.



Warranty
2-years

Ordering Information

Includes Timox Oxygen Timer, DISS Hand Tight on top, DISS Male at bottom
8050: Timox Oxygen Timer
8066: Replacement battery

Disposable Tubing Nipples



Clear 0119 **Yellow 0120** **Black 0121** **White 0122** **Green 0124**

Chain Ring Assembly



6" Chain with Closed Ring 8004

6" Chain with Open Ring 8005

Reusable Tubing Nipples



O₂ Hand Tight, Nipple 0154 **O₂ Wing Nut, Nipple 0158** **O₂ Hex Nut, Nipple 0159** **O₂ Knurled Nut, Nipple 0159K**
O₂ Hand Tight, Nipple with 5" chain 0154C **O₂ Wing Nut, Nipple with 5" chain 0158C** **O₂ Hex Nut, Nipple with 5" chain 0159C** **O₂ Knurled Nut, Nipple with 5" chain 0159KC**

Cleaning Methods

Part Number	Autoclave	Ethylene Oxide	Chlorine Dioxide	Hydrogen Peroxide	Gamma Ray	Electron Beam	Vaporized Hydrogen Peroxide (VHP)	Quaternary Cleaners	Sodium Hypochlorite "Bleach Solutions"
0154/ 0154C		✓	✓	✓	✓	✓	✓	✓	✓
0158/ 0158C		✓	✓	✓	✓	✓	✓	✓	✓
0159/ 0159C	✓	✓	✓	✓	✓	✓	✓	✓	✓
0115	✓	✓	✓	✓	✓	✓	✓	✓	✓

Please remove o-ring for autoclaving. Clean all tubing nipples after each patient use.